

APPLICATION DATA SHEET

BLACKFAST 716 LIGHT ALKALINE DEGREASER

USE: As supplied or 50% solution in water.

APPLICATION: Blackfast 716 is a light alkaline degreaser used in the preparation of clean metal surfaces prior to the blacking process. Used in a dilution of 50% in water for 15-20 minutes, Blackfast 716 will degrease iron and steels at room temperature. However, immersion times will vary according to the condition of the component. More heavily oiled and greased parts can be treated first using Blackfast 250, a solvent degreaser, and finished off effectively with Blackfast 716.

TANK MAINTENANCE It is important to maintain the strength of Blackfast 716 by removing 10% of the tank content every 1-2 weeks and replenishing with fresh material. The effectiveness of a Blackfast 716 tank can be checked regularly by examining the water rinsed components after degreasing. If water rinse drains unevenly showing dry patches, the surface is still contaminated with oil or grease and requires further degreasing through a fresh Blackfast 716 tank.

TANK MATERIAL Tanks should be made of mild steel or suitable grade of polypropylene.

PRODUCT SAFETY DATA SHEET: A safety data sheet is available.

Blackfast 716 is part of the Blackfast range of products for the treatment of iron, steel and aluminium at low temperatures.

Blackfast Chemicals continues to improve the quality and performance of its range of products and reserves the right to modify product formulations without prior notice.

OCTOBER 2002