



SAFETY DATA SHEET
BLACKFAST 925 WATER BASED OIL MEDIUM

Page: 1
Compilation date: 01/01/2011
Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BLACKFAST 925 WATER BASED OIL MEDIUM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Corrosion prevention for chemically blacked metal surfaces

1.3. Details of the supplier of the safety data sheet

Company name: Blackfast Chemicals Limited

78 Coombe Road

New Malden

Surrey

KT3 4QS

United Kingdom

Tel: +44 (0) 20 8336 2900

Fax: +44 (0) 20 8336 0909

Email: sales@blackfast.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 7985 975545

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R41; -: R52/53

Most important adverse effects: Risk of serious damage to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R41: Risk of serious damage to eyes.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S39: Wear eye / face protection.

SAFETY DATA SHEET

BLACKFAST 925 WATER BASED OIL MEDIUM

Page: 2

S23: Do not breathe spray.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Contains 4-(2-nitrobutyl)-morpholine. May produce an allergic reaction.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-METHYLPENTANE-2,4-DIOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-489-0	107-41-5	Xi: R36/38	-	2-10%

RESIDUAL OILS, PETROLEUM, OXIDISED

265-204-6	64742-99-0	Xi: R36	-	10-20%
-----------	------------	---------	---	--------

SODIUM SULPHONATE

271-781-5	68608-26-4	Xi: R41	-	2-10%
-----------	------------	---------	---	-------

ALCOHOL ETHOXYLATE

-	68155-01-1	Xi: R41	-	2-10%
---	------------	---------	---	-------

BARIUM SULPHONATE

263-140-3	61790-48-5	Xn: R20/22	-	2-10%
-----------	------------	------------	---	-------

N,N-METHYLENE BISMORPHOLINE

227-062-3	5625-90-1	Xn: R22; C: R34	-	2-10%
-----------	-----------	-----------------	---	-------

4-(2-NITROBUTYL)-MORPHOLINE

218-748-3	2224-44-4	Xn: R21/22; Xi: R38; Xi: R41; Sens.: R43; N: R50/53	-	<2%
-----------	-----------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

SAFETY DATA SHEET

BLACKFAST 925 WATER BASED OIL MEDIUM

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be vomiting and diarrhoea.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water fog. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

[cont...]

SAFETY DATA SHEET

BLACKFAST 925 WATER BASED OIL MEDIUM

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-METHYLPENTANE-2,4-DIOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	123 mg/m ³	123 mg/m ³	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Nitrile gloves.

Eye protection: Safety goggles.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Dark brown

Odour: Barely perceptible odour

Solubility in water: Reacts with water.

Boiling point/range°C: >100

Flash point°C: >100

Relative density: 1

pH: 7.5

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

BLACKFAST 925 WATER BASED OIL MEDIUM

Page: 5

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: Acids. Oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of nitrogen oxides. In combustion emits toxic fumes of sulphur oxides.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be vomiting and diarrhoea.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

[cont...]

SAFETY DATA SHEET

BLACKFAST 925 WATER BASED OIL MEDIUM

Page: 6

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 13 08 99

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: R20/22: Harmful by inhalation and if swallowed.
R21/22: Harmful in contact with skin and if swallowed.
R22: Harmful if swallowed.
R34: Causes burns.
R36/38: Irritating to eyes and skin.
R36: Irritating to eyes.
R38: Irritating to skin.
R41: Risk of serious damage to eyes.
R43: May cause sensitisation by skin contact.
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.